



Specification		Model	
		 1000M	 1000M
Description		OAM/IP GE Converter	OAM/IP GE Switch
Fiber interface	Single Mode	30/50/80/120km	10/20/40//50/80/120km
	Multimode	2Km	2Km
	WDM	20/40/60/80km	20/40/60/80km
	Wave Length (nm)	1310/1550	1310/1550
	Speed	1000Base-X	2x 1000Base-X SFP
	Transceiver Type	SFP-LC	SFP-LC
Copper interface	Speed	1000Base-T	2x 1000Base-T
	Connector	RJ45	RJ45
Features	Auto-Negotiation or force mode	V	V
	Auto MDI/MDIX	V	V
	Dying Gasp	V	V
	Bandwidth Control	V	V
	Loop back test	V	V
	IEEE 802.3x Flow Control	V	V
	Auto Laser Shutdown (ALS)	V	V
	Link fault pass through (LFP)	V	V
	RMON Counter	V	V
	Max. Packet Size (bytes)	10K	10K
	IEEE802.3ad LACP	V	V
	F/W upgrade via TFTP	V	V
	IEEE802.1Q VLAN	V	V
	IEEE802.1ad Q-in-Q VLAN	V	V
Management	In-band Management Protocol	IEEE 802.3ah OAM	IEEE 802.3ah OAM
	Console with CH01M	V	V
	Web	V	V
	Telnet	V	V
	SNMP/MIB	V	V
Operation Temperature		0~60 °C	0~60 °C
MTBF		65,000 hrs	65,000 hrs
Power		12VDC	12VDC
Dimension (D x W x H) mm		155 x 88 x 23	155 x 88 x 23