



FRM220-FTEC

E1/T1 + FE Fiber Multiplexer

The FRM220-FTEC is a T1 (US Standard) /E1 (European Standard) converter and timeslot cross connect which enables conversion between one T1 signal and one E1 signal. T1 and E1 signals with framing employ u-Law and A-Law compander encoding principles respectively and encode those analog (voice) signals into 64kbps digital data. The T1 interface supports D4(SF) or ESF frame formats with B8ZS or AMI line code. The E1 interface supports CCS (PCM31) or CAS (PCM30) framing without CRC-4 and framing with CRC-4. The line coding is HDB3.

Tests and diagnostics can easily be performed from the local console interface or via Web based management of the FRM220. Diagnostics include T1 local/remote and E1 local/remote loop back. When placed in a single slot chassis and used standalone without management, the card may be configured by DIP switches.

Features

- Converts between T1 and E1 data and signaling
- Enable equipment to operate at T1 and E1 rates
- Supports G.802 Annex B (T1 over E1)
- Configures A-law/ μ -law and signaling conversion
- Transparent conversion at 64kbps timeslot level
- Controlled slip for buffer over or under flow
- 24 time slots of T1 Nx64 can be inserted into E1 Nx64, 30/CAS or 31/CCS timeslots

Specifications

E1 Interface	Framing	CAS/PCM30 or CCS/PCM31 selectable	LEDs	PWR, Sys, Test, T1/E1										
	Bit rate	2.048Mbps		Standard	ITU-T G.703, G.704, G.706, G.823, G.824, ANSI T1.403									
	Line Code	HDB3			Power	12VDC								
	Line	75 ohm (BNC) / 120 ohm (RJ-45)				Power Consumption	< 6W							
	Impedance	Voice channel sample rule A-Law					Dimensions	Card: 155 x 20.8 x 88mm (D x W x H)						
	CRC check	CRC-4 enable/disable						Weight	130g					
	Pulse amplitude	Nominal 2.37V \pm 10% for 75ohm Nominal 3.00V \pm 10% for 120ohm							Temperature	0 ~ 50°C (Operating), -10 ~ 70°C (Storage)				
	Zero amplitude	\pm 0.1V								Humidity	10 ~ 90% non-condensing			
	Connector	RJ-45									Certification	CE, FCC		
	T1 Interface	Framing										D4, ESF selectable	MTBF	57,000 hrs
		Bit rate										1.544Mbps		
Line Code		B8ZS / AMI												
Equalization		0 ~ 655 feet settable Voice channel sample rule μ -Law												
CRC check		CRC-6 when ESF												
Line Impedance		100 ohms												
Transmit Pulse level		3.0V \pm 10%,												
Receive signal level		0 ~ -10dB												
Connector		RJ-45												

Application



Ordering Information

Model Name	Description
FRM220-FTEC	E1/T1 Cross rate converter

Note: This card must use CH01M, with serial console, to configure standalone settings. For standalone SNMP management, place this card in CH02/NMC chassis.