

Preliminary



IBP-202

Optical Bypass Switch



The IBP-202 Optical Bypass Switch is an industrial grade external bypass switch for optical-node failure in fiber optical network infrastructures. The IBP-202 Optical Bypass Switch prevents and saves communication from network failures during power loss. When power failure occurs, the Bypass switch will swiftly set to bypass mode and isolate the main-network from the local networking device (See Figure 1). Bypass switches are commonly used in some major optical networks, such as in railway communication systems, factory automation, and power substation, where fiber link failures are not tolerated.

Features

- Supports 100M/1G/10G optical bypass in SC/ST/LC connectors
- Optical bypass switching time <10ms with Low insertions loss
- Provides rotary switch to set delay boot time (0~180 seconds)
- Relay output for power failure warning
- Redundant dual DC input power 12/24/48VDC (9.6 ~ 60VDC)
- IP30 rugged metal housing and fanless
- Wide operating temperature -20 ~ 75°C
- Heavy industrial grade EMS, EMI, EN61000-6-2, EN61000-6-4, CE, FCC certified

Specifications

Fiber Connector	SC, ST, LC
Operating wavelength	1260 ~ 1360nm / 1510~1610nm
Optic Fiber cable	Single mode 8/125um, 9/125um
Insertion loss	<1.5dB
Optical Switching time	< 5ms
LED indicator	Power 1, Power 2, Alarm, Operation mode (Normal / Bypass)
Boot up delay adjuster	Provides a rotary switch to configure boot up delay time (0~180 seconds)
Relay contact	Power failure alarm
Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC
Removable Terminal Block	Provide for redundant power, Alarm relay contact
Power supply	12/24/48VDC (9.6~60VDC), Redundant power with polarity reverse protect function and removable terminal block
Reverse Polarity Protection	Supported for Power Input
Overload Current Protection	Supported
Power consumption	<2W
Housing	Rugged metal, IP30 protection and fanless
Weight	TBD
Installation	DIN Rail mounting, or wall mounting (Optional)
Operating Temperature	-20~75°C
Storage temperature	-40 ~ 85°C
Operating Humidity	5% ~ 95% (Non-condensing)
MTBF	TBD
Warranty	5 Years
Certification	
EMC	CE
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE

Immunity for Heavy Industrial Environment	EN61000-6-2
Emission for Heavy Industrial Environment	EN61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (EFT) Level 3, Criteria A EN61000-4-5 (Surge) Level 3, Criteria B EN61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF) Field strength 300A/m Criteria A
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

Application

The IBP-202 supports the function of optical path Normal mode and Bypass mode for fiber optical networks. It offers a simple mechanism to switch both of upload and down load fiber path when a power system failure occurred, and a path restores when power back. It offers a simple way to reduce the risk of optical network Node-Down which is caused by the power system.

Figure 1 :IBP-202 Data flow in Normal or Bypass mode




Figure 2 : Application example in line connection





Figure 3 : Application example in ring connection



Ordering Information

Model Name	Fiber connector			Power Input	Certification			Operating Temperature
	Connectortype	Connector Q'ty	Data rate	Redundant	EN61000-6-2 EN61000-6-4	CE	FCC	
IBP-202-SSC	SM SC	4	100M/Giga/10G	12/24/48VDC	V	V	V	-20~75°C
IBP-202-SST	SM ST	4	100M/Giga/10G	12/24/48VDC	V	V	V	-20~75°C
IBP-202-SLC	SM LC	4	100M/Giga/10G	12/24/48VDC	V	V	V	-20~75°C

Package List

- IBP-202 device
- Din Rail with screws
- Quickly installation guide
- Terminal block

Optional Accessories

Wall Mount Kit Accessories

IND-WMK02	Wall Mount kit for Industrial product, 184 x 50mm
-----------	---