



NDR-240-48
Output 48VDC, 240W

NDR-120-48
Output 48VDC, 120W

NDR-120-24
Output 24VDC, 120W

DR-4524
Output 24VDC, 45W

MDR-40-24
Output 24VDC, 40W

MDR-20-24
Output 24VDC, 20W



Having reliable and stable power for your industrial grade switches or converters is the best way to improve reliability and keep any down time to a minimum. CTC Union's safety certified AC to DC power supplies that are 100% compatible with all of our industrial grade switches and converters.

Features

- The series of industrial grade power supply have been fully tested with our industrial product for guaranteed compatibility and performance
- Universal AC input voltage range
- Protections: Short circuit / Overload / Over voltage/Over temperature
- Cooling by free air convection
- UL508, TUV, CB, CE safety approved
- Heavy industry grade EMS EN61000-6-2 approved
- 3 years warranty

Specifications

Model Name		NDR-240-48	NDR-120-48	NDR-120-24
Output	Dc Voltage	48V	48V	24V
	Rated Current	5A	2.5A	5A
	Current Range	0~5A	0~2.5A	0 ~ 5A
	Rated Power	240W	120W	120W
	Output Voltage Adj. Range	48~55VDC	48~55VDC	24 ~ 28VDC
Input	Voltage Range	90 ~ 264VAC / 127 ~ 370VDC	90~264VAC / 127~370VDC	90~264VAC / 127~370VDC
	Frequency Range	47 ~ 63Hz	47 ~ 63Hz	47 ~ 63Hz
	Efficiency (Typ.)	90%	89%	88%
Protection	Overload	105 ~ 130% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 130% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 130% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	Over Voltage	56 ~ 65V Protection type : Shut down o/p voltage, re-power on to recover	56~65V Protection type : Shut down o/p voltage, re-power on to recover	29 ~ 33V Protection type : Shut down o/p voltage, re-power on to recover
	Over Temperature	Shut down o/p voltage, recovers automatically after temperature goes down	Shut down o/p voltage, re-power on to recover	Shut down o/p voltage, re-power on to recover
Indicator	LED	DC OK	DC OK	DC OK
Housing	Dimension	113.5 x 63 x 125.2 mm (D x W x H)	113.5 x 40 x 125.2mm (D x W x H)	113.5 x 40 x 125.2mm (D x W x H)
	Installation Mounting	DIN Rail	DIN Rail	DIN Rail
	Working Temp	-20 ~ 70°C	-20 ~ 70°C	-20 ~ 70°C
Environment	Working Humidity	20 ~ 95% RH non-condensing	20 ~ 95% RH non-condensing	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-40 ~ 85°C, 10 ~ 95% RH	-40 ~ 85°C, 10 ~ 95% RH	-20 ~ 85°C, 10 ~ 95% RH
	Vibration	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6
	Safety Standards	UL508, TUV EN60950-1 approved	UL508, TUV EN60950-1 approved	UL508, TUV EN60950-1 approved
Safety & EMC	Withstand Voltage	I/P-O/P:3KVAC, I/P-FG:2KVAC, O/P-FG: 0.5KVAC	I/P-O/P:3KVAC, I/P-FG:2KVAC, O/P-FG: 0.5KVAC	I/P-O/P:3KVAC, I/P-FG:2KVAC, O/P-FG: 0.5KVAC
	Isolation Resistance	I/P-O/P, I/P-FG, O/P-FG >100M Ohm /500VD@25°C/ 70% RH	I/P-O/P, I/P-FG, O/P-FG >100M Ohm /500VD@25°C/ 70% RH	I/P-O/P, I/P-FG, O/P-FG >100M Ohm /500VD@25°C/ 70% RH
	EMC Emission	Compliance to EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2, -3	Compliance to EN55022 (CISPR22) Class B, EN61000-3-2,-3	Compliance to EN55022 (CISPR22) Class B, EN61000-3-2,-3
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, (EN50082-2), heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2 (EN50082-2) heavy industry level, criteria A
	PFC	Built in Active PFC		
Others	MTBF	230.2K Hours MIL-HDBK-217F (25°C)	453.3K Hours MIL-HDBK-217F (25°C)	453.3K Hours MIL-HDBK-217F (25°C)
	Waranty	3 Years	3 Years	3 Years

Model Name	DR-4524	MDR-40-24	MDR-20-24
Output	Dc Voltage	24V	24V
	Rated Current	2A	1.7A
	Current Range	0 ~ 2A	0~1.7A
	Rated Power	48W	40.8W
	Output Voltage Adj. Range	21.6 ~ 26.4VDC	24~30VDC
Input	Voltage Range	85 ~ 264VAC / 120 ~ 370VDC	85 ~ 264VAC / 120 ~ 370VDC
	Frequency Range	47 ~ 63Hz	47 ~ 63Hz
	Efficiency (Typ.)	80%	88%
Protection	Overload	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed	105 ~ 150% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	Over Voltage	27.6 ~ 32.4V Protection type : Shut off o/p voltage, clamping by zener diode	31.2~36V Protection type : Shut down o/p voltage, re-power on to recover
Alarm Relay	DC OK Relay	DC OK Relay will Close In Normal Relay contact rating(max.) : 30V/1A resistive	DC OK Relay will Close In Normal Relay contact rating(max.) : 30V/1A resistive
Indicator	LED	Power On	DC OK
Housing	Dimension	67 x 78 x 93 mm (D x W x H)	100 x 40 x 90mm (D x W x H)
	Installation Mounting	DIN Rail	DIN Rail
Environment	Working Temp	-10 ~ 50°C	-20 ~ 70°C
	Working Humidity	20 ~ 90% RH non-condensing	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-20 ~ 85°C , 10 ~ 95% RH	-40 ~ 85°C , 10 ~ 95% RH
	Vibration	Compliance to IEC60068-2-6	Compliance to IEC60068-2-6
Safety & EMC	Safety Standards	UL508 approved	UL508, UL60950-1, TUV EN60950-1 approved
	Withstand Voltage	I/P-O/P:3KVAC, I/P-FG:2KVAC, O/P-FG:0.5KVAC	I/P-O/P:3KVAC, I/P-FG:2KVAC, O/P-FG:0.5KVAC
	Isolation Resistance	I/P-O/P, I/P-FG, O/P-FG >100M Ohm /500VD@25°C/ 70% RH	I/P-O/P, I/P-FG, O/P-FG >100M Ohm /500VD@25°C/ 70% RH
	EMC Emission	Compliance to EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2, -3	Compliance to EN55011, EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2,-3
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2 (EN50082-2), heavy industry level, criteria A	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024, EN61000-6-2, EN61204-3, heavy industry level, criteria A
Others	PFC		
	MTBF	364.6K hrs MIL-HDBK-217F (25°C)	301.7K Hours MIL-HDBK-217F (25°C)
	Waranty	3 Years	3 Years

Ordering Information

Model Name	Input Voltage Range	Output Voltage	Output Voltage Adj. Range	Output Power	Operating Temperature
NDR-240-48	90 ~ 264VAC / 127 ~ 370VDC	48VDC	48~55VDC	240W	-20~ 70°C
NDR-120-48	90 ~ 264VAC / 127 ~ 370VDC	48VDC	48~55VDC	120W	-20~ 70°C
NDR-120-24	90 ~ 264VAC / 127 ~ 370VDC	24VDC	24~28VDC	120W	-20~ 70°C
DR-4524	85 ~ 264VAC / 120 ~ 370VDC	24VDC	21.6~26.4VDC	48W	-10~ 50°C
MDR-40-24	85 ~ 264VAC / 120 ~ 370VDC	24VDC	24~30VDC	40W	-20~ 70°C
MDR-20-24	85 ~ 264VAC / 120 ~ 370VDC	24VDC	21.6~26.4VDC	24W	-20~ 70°C