

# BUK1-RJ/M12/USB

## Auto Backup Kit for CTC Managed Switch with RJ45/M12/USB Connector

- » RS232 RJ45 Type Console Connection (BUK1-RJ)
- » RS232 M12 Type Console Connection (BUK1-M12)
- » USB Type C Console Connection (BUK1-USB)
- » Powered by USB
- » Plug & Play Operation
- » Supports CTC Managed Switch for Auto Backup and Restore Configuration

NEW



The automatic backup configuration kit - BUK1 series is designed to save, download and upload the setup configurations of CTCU managed Ethernet switches series through the RS-232 or USB console port. Easily back up or restore the Ethernet switch's system parameters and configuration by simply pressing a button on the BUK1. It is a greatly simplified design that enhances network deployment and maintenance processes, thereby reducing system downtime and costs.

### Features

- Push button for start to upload/download configuration
- DIP SW for upload/download configuration selection

### Specifications


<b>DIP SW</b>	DIP 1	OFF: Download Configuration ON : Upload Configuration
	DIP 2	Reserve
<b>Push Button</b>	For Power On/Off, or start to process	
	Push long time for power on or power off (Toggle type switch)	
	Push short time for start to upload/download configuration	
<b>Connector</b>	1x RJ45 RS232	With RJ45-to-R45 (Pin to Pin) cable for RJ45 console managed switch (BUK1-RJ) With RJ45-to-M12 cable for M12 console managed switch (BUK1-M12)
	1x USB	With USB Type A to USB Type C cable for USB console managed switch (BUK1-USB)
<b>LED</b>	Power	ON: Power Good (Green)
		Blank: Power in Charged (Green)
		Blank : Battery Low (Red)
	Status	Blinking: Process (Green)
		ON: Process Success (Green)
		Blinking: Device Not Match (Red)
		ON: Fail (Red)
<b>Power Supply</b>	Powered by USB Type C	
<b>Operating Temperature</b>	-10 ~ 60°C	
<b>Operating Humidity</b>	5% to 95% (Non-condensing)	
<b>Storage Temperature</b>	-40 ~ 85°C	
<b>Housing</b>	Rugged Metal, IP30 Protection and Fanless	
<b>Dimensions</b>	30 x 72 x 26.8mm (D x W x H)	
<b>Weight</b>	TBD	
<b>MTBF</b>	TBD (MIL-HDBK-217)	
<b>Warranty</b>	5 years	

# Auto Backup Kit

## Certification

EMC/EMS	CE (EN55032, EN55035)
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B
	EN61000-4-3 (RS) Level 3, Criteria A
	EN61000-4-4 (Burst) Level 3, Criteria A
	EN61000-4-5 (Surge) Level 3, Criteria B
	EN61000-4-6 (CS) Level 3, Criteria A
	EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A

## Dimensions



## Ordering Information

Model Name	Connector for Switch Console		Push Button	DIP SW	Power	Certification	Operating Temperature
	Port	Cable	Power / Start	Upload/ Download	Powered by USB	CE & FCC	
BUK1-RJ	RJ45	RJ45 to RJ45	1	1	Type C	V	-10 ~ 60°C
BUK1-M12	RJ45	RJ45 to M12	1	1	Type C	V	-10 ~ 60°C
BUK1-USB	USB Type A	USB Type A to USB Type C	1	1	Type C	V	-10 ~ 60°C

### Package List

#### BUK1-RJ

- 1x BUK1 device
- 1x RJ45-to-RJ45 pin-to-pin Cable 30cm

#### BUK1-M12

- 1x BUK1 device
- 1x RJ45-to-M12 Cable 30cm

#### BUK1-USB

- 1x BUK1 device
- USB Type A to USB Type C Cable 30cm