

## 24x GbE RJ45 + 8x 100/1000Base-X SFP

- » Supports IEEE 1588 PTP V2
- » Supports u-Ring , ERPS, EPS, MSTP, RSTP, STP for Redundant Cabling
- » EN62368-1, EN50121-4, EN61000-6-2, EN61000-6-4, CE and FCC Certified
- » 4KV Surge Protection for RJ45 and SFP Ports
- » 2.25K VDC Hi-Pot Isolation Protection for Ethernet Ports and Power
- » Supports Negative Voltage Power Input



As an industrial Layer 2 Ethernet switch for process and transportation automation applications, IGS-2408SM supports static and dynamic routing protocols, features 24 Gigabit UTP ports and 8 100/1000Mbps SFP slots, fanless design and redundancy Isolated power supplies, certified to many industry-grade standards, are ideal for deployment in harsh environments to provide mission-critical network services.

## Features

- Redundant isolated 24/48/-48VDC (18~60VDC), or/and isolated 110/220VAC power inputs
- STP, RSTP, MSTP, ITU-T G.8032 Ethernet Ring Protection Switching (ERPS) for network redundancy
- Provides 14 instances each can support  $\mu$ -Ring,  $\mu$ -Chain or Sub-Ring for flexible networking applications
- $\mu$ -Ring redundancy, recovery time <20ms in 250 devices
- Supports EMS Management

## Specifications

| Standard              |  |                                                                                   |
|-----------------------|--|-----------------------------------------------------------------------------------|
| IEEE 802.3            |  | 10Base-T 10Mbit/s Ethernet                                                        |
| IEEE 802.3u           |  | 100Base-TX, 100Base-FX, Fast Ethernet                                             |
| IEEE 802.3ab          |  | 1000Base-T Gbit/s Ethernet over twisted pair                                      |
| IEEE 802.3z           |  | 1000Base-X Gbit/s Ethernet over Fiber-Optic                                       |
| IEEE 802.1d           |  | STP (Spanning Tree Protocol)                                                      |
| IEEE 802.1w           |  | RSTP (Rapid Spanning Tree Protocol )                                              |
| IEEE 802.1s           |  | MSTP (Multiple Spanning Tree Protocol)                                            |
| ITU-T G.8032 / Y.1344 |  | ERPS (Ethernet Ring Protection Switching)                                         |
| ITU-T G.8031 / Y.1342 |  | EPS (Ethernet Protection Switching)                                               |
| IEEE 802.1Q           |  | Virtual LANs (VLAN)                                                               |
| IEEE 802.1X           |  | Port based and MAC based Network Access Control, Authentication                   |
| IEEE 802.3ac          |  | Max frame size extended to 1522Bytes                                              |
| IEEE 802.3ad          |  | Link aggregation for parallel links with LACP (Link Aggregation Control Protocol) |
| IEEE 802.3X           |  | Flow control for full duplex                                                      |
| IEEE 802.1ad          |  | Stacked VLANs, Q-in-Q                                                             |
| IEEE 802.1p           |  | LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization                           |
| IEEE 802.1ab          |  | Link Layer Discovery Protocol (LLDP)                                              |
| IEEE 802.3az          |  | EEE (Energy Efficient Ethernet)                                                   |

# Industrial GbE Switch

|                                                              |                                                                                                                                                                                                                                                                                                                                |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>VLAN ID</b>                                               | 4094 IEEE 802.1Q VLAN ID                                                                                                                                                                                                                                                                                                       |
| <b>Switch Architecture</b>                                   | Back-plane (Switching Fabric): 64Gbps (Full wire-speed)                                                                                                                                                                                                                                                                        |
| <b>Data Processing</b>                                       | Store and Forward                                                                                                                                                                                                                                                                                                              |
| <b>Network Connector</b>                                     | <b>SFP:</b><br>8x 100/1000Base-X SFP socket, Support DDMI<br><b>RJ45:</b><br>24x 10/100/1000Base-T RJ-45, Support Auto negotiation speed, Auto MDI/MDI-X function                                                                                                                                                              |
| <b>Console</b>                                               | RS-232 (RJ-45)                                                                                                                                                                                                                                                                                                                 |
| <b>Network Cable</b>                                         | UTP/STP Cat.5e cable or above<br>EIA/TIA-568 100-ohm (100meter)                                                                                                                                                                                                                                                                |
| <b>Protocols</b>                                             | CSMA/CD                                                                                                                                                                                                                                                                                                                        |
| <b>Reverse Polarity Protection</b>                           | For input power                                                                                                                                                                                                                                                                                                                |
| <b>Overload Current Protection</b>                           | Supported                                                                                                                                                                                                                                                                                                                      |
| <b>Power Supply</b>                                          | Redundant 2x AC input power (-AA model)<br>Redundant 1x AC and 1x DC input power (-AD model)<br>Redundant 2x DC input power (-DD model)<br>AC input power (A) : Isolated 110/220VAC (85VAC~264VAC)<br>DC input power (D) : Isolated 24/48/-48VDC (18~60VDC), Removable Terminal Block<br>Supports negative voltage power input |
| <b>Power Consumption</b>                                     | < 30W                                                                                                                                                                                                                                                                                                                          |
| <b>LED</b>                                                   | System: Power 1 (Green), Power 2 (Green), Act /Alarm (Green/Amber), Ring Master (Green)<br><b>P1~P24</b> UTP: 10/100 Link/Active (Green), 1000 Link/Active (Amber)<br><b>P25~P32</b> SFP Slot: 100 /1000Base-X, Link/Active (Amber)                                                                                            |
| <b>Jumbo Frame</b>                                           | 10K Byte                                                                                                                                                                                                                                                                                                                       |
| <b>MAC Address Table</b>                                     | 32K                                                                                                                                                                                                                                                                                                                            |
| <b>Memory Buffer</b>                                         | 4M Bytes for packet buffer                                                                                                                                                                                                                                                                                                     |
| <b>Device Memory</b>                                         | 16M Bytes Flash ROM, 1G Bytes RAM                                                                                                                                                                                                                                                                                              |
| <b>Warning Message</b>                                       | System Syslog, SMTP / e-mail event message, alarm relay                                                                                                                                                                                                                                                                        |
| <b>Alarm Relay Contact</b>                                   | Relay outputs with current carrying capacity of 1A @24VDC, 2-Pin removable terminal block                                                                                                                                                                                                                                      |
| <b>Operating Temperature</b>                                 | -40 ~ 75°C (IGS-2408SM-E)<br>-10 ~ 60°C (IGS-2408SM)                                                                                                                                                                                                                                                                           |
| <b>Operating Humidity</b>                                    | 5% to 95% (Non-condensing)                                                                                                                                                                                                                                                                                                     |
| <b>Storage Temperature</b>                                   | -40 ~ 85°C                                                                                                                                                                                                                                                                                                                     |
| <b>Housing</b>                                               | Rugged Metal, IP30 Protection and Fanless                                                                                                                                                                                                                                                                                      |
| <b>Dimensions</b>                                            | 280 x 440 x 44mm (D x W x H)                                                                                                                                                                                                                                                                                                   |
| <b>Weight</b>                                                | 4.755kg (IGS-2408SM-(E)AA)<br>4.51kg (IGS-2408SM-(E)AD)<br>4.26kg (IGS-2408SM-(E)DD)                                                                                                                                                                                                                                           |
| <b>Installation Mounting</b>                                 | 19" rack mount                                                                                                                                                                                                                                                                                                                 |
| <b>MTBF</b>                                                  | 103,057 Hours (IGS-2408SM-AA)<br>103,451 Hours (IGS-2408SM-AD)<br>103,447 Hours (IGS-2408SM-DD)<br>(MIL-HDBK-217)                                                                                                                                                                                                              |
| <b>Warranty</b>                                              | 5 years                                                                                                                                                                                                                                                                                                                        |
| <b>Certification</b>                                         |                                                                                                                                                                                                                                                                                                                                |
| <b>EMC</b>                                                   | CE (EN55032, EN55035)                                                                                                                                                                                                                                                                                                          |
| <b>EMI (Electromagnetic Interference)</b>                    | FCC Part 15 Subpart B Class A, CE                                                                                                                                                                                                                                                                                              |
| <b>Railway Traffic</b>                                       | EN50121-4                                                                                                                                                                                                                                                                                                                      |
| <b>Immunity for Heavy Industrial Environment</b>             | EN61000-6-2                                                                                                                                                                                                                                                                                                                    |
| <b>Emission for Heavy Industrial Environment</b>             | EN61000-6-4                                                                                                                                                                                                                                                                                                                    |
| <b>EMS (Electromagnetic Susceptibility) Protection Level</b> | EN61000-4-2 (ESD) Level 3, Criteria B<br>EN61000-4-3 (RS) Level 3, Criteria A<br>EN61000-4-4 (Burst) Level 3, Criteria A<br>EN61000-4-5 (Surge) Level 3, Criteria B<br>EN61000-4-6 (CS) Level 3, Criteria A<br>EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A                                           |
| <b>Safety</b>                                                | EN62368-1                                                                                                                                                                                                                                                                                                                      |

# Industrial GbE Switch

|                             |                                                                        |
|-----------------------------|------------------------------------------------------------------------|
| <b>Hi Pot Protection</b>    | DC 2.25KV for power to chassis ground, Ethernet port to chassis ground |
| <b>4KV Surge Protection</b> | Supported for RJ45 and SFP ports                                       |
| <b>Shock</b>                | IEC 60068-2-27                                                         |
| <b>Freefall</b>             | IEC 60068-2-32                                                         |
| <b>Vibration</b>            | IEC 60068-2-6                                                          |

## Software Specifications

### Topology

|                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>VLAN</b>                                                      | IEEE 802.1q VLAN, up to 4094 802.1Q VLAN ID<br>IEEE 802.1q VLAN, up to 4094 Groups<br>IEEE 802.1ad Q-in-Q<br>MAC-based VLAN, up to 256 entries<br>IP Subnet-based VLAN, up to 128 entries<br>Protocol-based VLAN (Ethernet, SNAP, LLC), up to 128 entries<br>VLAN Translation, up to 256 entries<br>Private VLAN for port isolation<br>GVRP (GARP VLAN Registration Protocol)<br>MVR (Multicast VLAN Registration)<br>Voice VLAN |
| <b>Link Aggregation (Port Trunk)</b>                             | Static (Hash with SA, DA, IP, TCP/UDP port), Maximum trunk group : 16group<br>Dynamic (IEEE 802.3ad LACP), Maximum trunk group : 16group<br>Per group up-to 8 port                                                                                                                                                                                                                                                               |
| <b>Spanning Tree</b>                                             | IEEE 802.1d STP, IEEE 802.1w RSTP, IEEE 802.1s MSTP                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Multiple <math>\mu</math>-Ring</b>                            | Up to 14 instances each support $\mu$ -Ring, $\mu$ -Chain or Sub-Ring for flexible networking applications<br>Recovery time <20ms<br>The maximum number of device is allowed 250 nodes in a Ring.                                                                                                                                                                                                                                |
| <b>Loop Protection</b>                                           | Supported                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection)</b>     | Recovery time <20ms<br>Single Ring, Sub-Ring, Multiple ring topology                                                                                                                                                                                                                                                                                                                                                             |
| <b>ITU-T G.8031 / Y.1342 EPS (Ethernet Protection Switching)</b> | Supported                                                                                                                                                                                                                                                                                                                                                                                                                        |

### QoS Features

|                                      |                                                                                                                                                                                                                     |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Class of Service</b>              | IEEE 802.1p 8 active priorities queues per port                                                                                                                                                                     |
| <b>Traffic Classification QoS</b>    | IEEE 802.1p based CoS<br>IP Precedence based CoS<br>IP DSCP based CoS<br>QCL (QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI, Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number |
| <b>Bandwidth Control for Ingress</b> | Per port based                                                                                                                                                                                                      |
| <b>Bandwidth Control for Egress</b>  | Per port based<br>Per queue / Per port shaper                                                                                                                                                                       |
| <b>DiffServ (RF 2474) Remarking</b>  |                                                                                                                                                                                                                     |
| <b>Storm Control</b>                 | For Unicast, Broadcast and Multicast                                                                                                                                                                                |

### IP Multicasting Features

|                            |                                                                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>IGMP / MLD Snooping</b> | IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2<br>Port Filtering Profile<br>Throttling, Fast Leave<br>Maximum Multicast Group : up to 1022 entries<br>Query / Static Router Port |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Security Features

|                    |                         |
|--------------------|-------------------------|
| <b>IEEE 802.1X</b> | Port-Based<br>MAC-Based |
|--------------------|-------------------------|

# Industrial GbE Switch

|                                              |                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>ACL</b>                                   | Number of rules : up to 256 entries<br>for L2 / L3 / L4<br>L2 : Mac address SA/DA/VLAN<br>L3 : IP address SA/DA, Subnet<br>L4 : TCP/UDP                                                                                                                                                                                 |
| <b>RADIUS</b>                                | Authentication & Accounting                                                                                                                                                                                                                                                                                             |
| <b>TACACS+</b>                               | Authentication, Authorization and Accounting                                                                                                                                                                                                                                                                            |
| <b>HTTPS, HTTP</b>                           | Supported                                                                                                                                                                                                                                                                                                               |
| <b>SSL / SSH v2</b>                          | Supported                                                                                                                                                                                                                                                                                                               |
| <b>User Name Password Authentication</b>     | Local Authentication<br>Remote Authentication (via RADIUS / TACACS+)                                                                                                                                                                                                                                                    |
| <b>Management Interface Access Filtering</b> | Web, Telnet / SSH, CLI RS-232 console                                                                                                                                                                                                                                                                                   |
| <b>Management Features</b>                   |                                                                                                                                                                                                                                                                                                                         |
| <b>CLI</b>                                   | Cisco® like CLI                                                                                                                                                                                                                                                                                                         |
| <b>Web UI</b>                                | Supported                                                                                                                                                                                                                                                                                                               |
| <b>Telnet</b>                                | Server                                                                                                                                                                                                                                                                                                                  |
| <b>SNMP</b>                                  | V1, V2c, V3                                                                                                                                                                                                                                                                                                             |
| <b>sFlow</b>                                 | Supported                                                                                                                                                                                                                                                                                                               |
| <b>Modbus/TCP</b>                            | Supports management and monitoring                                                                                                                                                                                                                                                                                      |
| <b>SW &amp; Configuration Upgrade</b>        | TFTP, HTTP<br>Redundant firmware in case of upgrade failure                                                                                                                                                                                                                                                             |
| <b>RMON</b>                                  | RMON I (1, 2, 3, 9 group), RMON II                                                                                                                                                                                                                                                                                      |
| <b>MIB</b>                                   | RFC1213 MIB II, Private MIB                                                                                                                                                                                                                                                                                             |
| <b>UPnP</b>                                  | Supported                                                                                                                                                                                                                                                                                                               |
| <b>DHCP</b>                                  | Server/Client/Relay/Relay option 82/Snooping                                                                                                                                                                                                                                                                            |
| <b>Warning Message</b>                       | System syslog, e-mail, alarm relay                                                                                                                                                                                                                                                                                      |
| <b>DNS</b>                                   | Client, Proxy                                                                                                                                                                                                                                                                                                           |
| <b>IEEE1588 PTP V2</b>                       | Supports 5 operating mode in each port :<br>Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master and Slave                                                                                                                                                                           |
| <b>IP Source Guard</b>                       | Supported                                                                                                                                                                                                                                                                                                               |
| <b>Mirroring</b>                             | Local and Remote                                                                                                                                                                                                                                                                                                        |
| <b>Event Syslog</b>                          | Syslog server (RFC3164) (Support 4 server)                                                                                                                                                                                                                                                                              |
| <b>NTP V4.0, SNTP</b>                        | Client                                                                                                                                                                                                                                                                                                                  |
| <b>LLDP (IEEE 802.1ab)</b>                   | Link Layer Discovery Protocol<br>LLDP-MED                                                                                                                                                                                                                                                                               |
| <b>IPv6 Features</b>                         |                                                                                                                                                                                                                                                                                                                         |
| <b>IPv6 Management</b>                       | Telnet Server/ICMP v6                                                                                                                                                                                                                                                                                                   |
| <b>SNMP over IPv6</b>                        | Supported                                                                                                                                                                                                                                                                                                               |
| <b>HTTP over IPv6</b>                        | Supported                                                                                                                                                                                                                                                                                                               |
| <b>SSH over IPv6</b>                         | Supported                                                                                                                                                                                                                                                                                                               |
| <b>IPv6 Telnet</b>                           | Supported                                                                                                                                                                                                                                                                                                               |
| <b>IPv6 NTP, SNTP</b>                        | Client                                                                                                                                                                                                                                                                                                                  |
| <b>IPv6 TFTP</b>                             | Supported                                                                                                                                                                                                                                                                                                               |
| <b>IPv6 QoS</b>                              | Supported                                                                                                                                                                                                                                                                                                               |
| <b>IPv6 ACL</b>                              | Number of rules: up to 256 entries<br>for L2 / L3 / L4<br>L2 : Mac address SA/DA/VLAN<br>L3 : IP address SIP, Subnet (32bit)<br>L4 : TCP/UDP                                                                                                                                                                            |
| <b>Other Features</b>                        | <b>Green Ethernet</b><br>Supports IEEE 802.3az EEE (Energy Efficient Ethernet)<br>Management to optimize the power consumption<br>Determine the cable length and lowering the power for ports with short cables<br>Lower the power for a port when there is no link<br>LED Power Management : Adjustment LEDs intensity |

# Industrial GbE Switch

4

## Dimensions

Front View



Rear View

-AA Power




-DD Power




-AD Power



Top View



Side View



## Ordering Information

| Model Name      | Managed | Total Port | RJ45               | SFP             | Input Power   |             | Certification    |        |                                   | Operating Temperature |
|-----------------|---------|------------|--------------------|-----------------|---------------|-------------|------------------|--------|-----------------------------------|-----------------------|
|                 |         |            | 10/100/1000 Base-T | 100/1000 Base-X | 24/48/-48 VDC | 110/220 VAC | Safety EN62368-1 | CE FCC | EN50121-4 EN61000-6-2 EN61000-6-4 |                       |
| IGS-2408SM-E-AA | V       | 32         | 24                 | 8               |               | 2           | V                | V      | V                                 | -40~75°C              |
| IGS-2408SM-E-AD | V       | 32         | 24                 | 8               | 1             | 1           | V                | V      | V                                 | -40~75°C              |
| IGS-2408SM-E-DD | V       | 32         | 24                 | 8               | 2             |             | V                | V      | V                                 | -40~75°C              |
| IGS-2408SM-AA   | V       | 32         | 24                 | 8               |               | 2           | V                | V      | V                                 | -10~60°C              |
| IGS-2408SM-AD   | V       | 32         | 24                 | 8               | 1             | 1           | V                | V      | V                                 | -10~60°C              |
| IGS-2408SM-DD   | V       | 32         | 24                 | 8               | 2             |             | V                | V      | V                                 | -10~60°C              |

## Optional Accessories

### Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with all CTC Union industrial grade Ethernet switches for guaranteed compatibility and performance. Best performance can be guaranteed, even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheets for more items and detailed information.)

|                    |                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------|
| ISFP-M7000-85-D(E) | Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDMI, -10~70°C (-40~85°C) |
| ISFP-S7020-31-D(E) | Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDMI, -10~70°C (-40~85°C)          |
| ISFP-T7T00-00-(E)  | Industrial SFP 10/100/1000Base-T UTP 100meter, -10~70°C (-40~85°C)                                      |
| ISFP-M5002-31-D(E) | Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDMI, -10~70°C (-40~85°C)        |
| ISFP-S5030-31-D(E) | Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDMI, -10~70°C (-40~85°C)                   |

### Industrial Power Supply

|            |                                                                                                |
|------------|------------------------------------------------------------------------------------------------|
| NDR-120-48 | Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 120W, -20 ~ 70°C (For DC type) |
|------------|------------------------------------------------------------------------------------------------|