

IGS-A804XSM-8PH

8x GbE RJ45 + 4x 100M/1G/2.5G/10G SFP with 8x PoE 240W, 48VDC

NEW

- ◆ Compliant with the IEC 62443-4-2* industrial cybersecurity standards
- ◆ Supports IEEE 1588 PTP V2
- ◆ Supports μ -Ring, ERPS, APS, MRP, MSTP, RSTP, STP for Redundant Cabling
- ◆ Auto Checking and Auto Reset When PoE PD Fail
- ◆ EN50121-4, EN61000-6-2, EN61000-6-4, CE and FCC Certified
- ◆ 4KV Surge Protection for PoE, RJ45 and SFP Ports
- ◆ Supports Secure Boot



The industrial cyber-hardened managed PoE switch IGS-A804XSM-8PH is one of our new generation designs and comes with 8 gigabit UTP ports, each complies with IEEE802.3af/at up to 30W PoE+ standard. Equipped with 4 100M/1G/2.5G/10G SFP slots for fiber optic connectivity meet the requirements for extended transmission distance, fanless design, high MTBF, 4KV surge protection and supports wide temperature operation, 48VDC redundant power input, and is designed to comply with cybersecurity regulations. Suitable for heavy-duty applications in harsh environments such as industrial factory automation, data centers, smart transportation systems, military and utility market applications beyond environmental conditions commercial product specifications.

Features

- 48VDC (44~57VDC) redundant dual power input
- Provides 8-port IEEE 802.3af / 802.3at PoE+ output (30W per port, total 240W)
- Provides 5 ring instances that each can support μ -Ring, μ -Chain or Sub-Ring type for flexible uses. Supports up to 5 rings in one device (Please see CTC μ -Ring white paper for more details and more topology application)
- μ -Ring for redundant cabling, recovery time < 20ms in 250 devices
- Supports EMS Management
- The 10 Gigabit Ethernet optical interface shall support a transmission distance of at least 10 km.
- The system triggers instant alarms for power or communication failures and transmits real-time signal to the outdoor managed switch NMS.

Specifications

Standard	IEEE 802.3	10Base-T 10Mbit/s Ethernet
	IEEE 802.3u	100Base-TX, 100Base-FX, Fast Ethernet
	IEEE 802.3ab	1000Base-T Gbit/s Ethernet over twisted pair
	IEEE 802.3z	1000Base-X Gbit/s Ethernet over Fiber-Optic
	IEEE 802.3cb	2.5GBase-X
	IEEE 802.3ae	10G bit/s Ethernet over fiber
	IEEE 802.3af	PoE (Power over Ethernet)
	IEEE 802.3at	PoE+ (Power over Ethernet enhancements)
	IEEE 802.1D	STP (Spanning Tree Protocol)
	IEEE 802.1W	RSTP (Rapid Spanning Tree Protocol)
	IEEE 802.1S	MSTP (Multiple Spanning Tree Protocol)
	ITU-T G.8032 / Y.1344	ERPS (Ethernet Ring Protection Switching)
	ITU-T G.8031 / Y.1342	APS (Automatic Protection Switching)

Industrial Managed 10G PoE Switch



Standard	IEEE 802.1Q	Virtual LANs (VLAN)										
	IEEE 802.1X	Port based and MAC based Network Access Control, Authentication										
	IEEE 802.3ac	Max frame size extended to 1522Bytes										
	IEEE 802.3ad	Link aggregation for parallel links with LACP (Link Aggregation Control Protocol)										
	IEEE 802.3x	Flow control for Full Duplex										
	IEEE 802.1ad	Stacked VLANs, Q-in-Q										
	IEEE 802.1p	LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization										
	IEEE 802.1ab	Link Layer Discovery Protocol (LLDP)										
Switch Architecture	Back-Plane (Switching Fabric): 96Gbps (Full Wire-Speed)											
Forwarding Rate	71.4Mpps											
Data Processing	Store and Forward											
Flow Control	IEEE 802.3x for full duplex mode Back pressure for half duplex mode											
Network Connector	8x 10/100/1000Base-T RJ-45 + 4x 100M/1G/2.5G/10G SFP											
	RJ-45 UTP port supports Auto negotiation speed, Auto MDI/MDI-X function											
	SFP port supports 100M/1G/2.5G/10G speed with DDMI											
Storage Port	USB type A											
Console Port	USB type C											
PoE Standard & RJ-45 Pin Assignment	8x IEEE 802.3af /IEEE 802.3at											
	2 pairs PoE, PoE+, 30W/port End-Span, Alternative A mode. Positive (V+) : RJ-45 pin 1, 2. Negative (V-) : RJ-45 pin 3, 6.											
Network Cable	UTP/STP Cat. 5e cable or above											
	EIA/TIA-568 100-ohm (100meter)											
Protocols	CSMA/CD											
Reverse Polarity Protection	Supported for power input											
Overload Current Protection	Supported											
CPU Watch Dog	Supported											
Power Supply	Redundant Dual power input (Removable terminal block) 48VDC (44~57VDC) (50~57V input is recommended for IEEE802.3at PoE+ applications)											
Power Consumption	<table border="1"> <thead> <tr> <th>Input Voltage</th> <th>Total Power Consumption</th> <th>Device Power Consumption</th> <th>PoE Budget</th> </tr> </thead> <tbody> <tr> <td>50VDC</td> <td>265W</td> <td>21W</td> <td>240W</td> </tr> </tbody> </table>				Input Voltage	Total Power Consumption	Device Power Consumption	PoE Budget	50VDC	265W	21W	240W
	Input Voltage	Total Power Consumption	Device Power Consumption	PoE Budget								
50VDC	265W	21W	240W									
PoE Power Budget	Maximum PoE Output power budget 30W/port, Total 240W											
LED	System: Power 1 (Green), Power 2 (Green), Alarm (Amber), CPU Act (Green), Ring Master (Green)											
	UTP: 10/100 Link/Active (Green), 1000 Link/Active (Amber)											
	SFP Slot: 100M/1G Link/Active (Green), 2.5G/10G Link/Active (Amber)											
	PoE: ON (Green)											
Jumbo Frame	10KB											
MAC Address Table	16K											
Memory Buffer	12Mb for packet buffer											
Device Memory	4G Bytes eMMC, 2G Bytes RAM											
Warning Message	System Syslog, SMTP/ e-mail event message, alarm relay											
Alarm Relay Contact	Relay outputs with current carrying capacity of 1A @24VDC											
Removable Terminal Block	Provides 1 terminal block for Alarm relay, redundant power PWR1 and PWR2											
Operating Temperature	-10 ~ 60°C											
Operating Humidity	5% to 95% (Non-condensing)											
Storage Temperature	-40 ~ 85°C											
Housing	Rugged Metal, IP30 Protection, Fanless											
Dimensions	106 x 72 x 152mm (D x W x H)											
Weight	1,230g											
Installation Mounting	DIN Rail mounting or wall mounting (Optional)											
MTBF (MIL-HDBK-217)	301,421											
Warranty	5 years											

Certification

Industrial Cybersecurity	IEC 62443-4-1, IEC 62443-4-2*
EMC	CE (EN55032, EN55035)
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE
Railway Traffic	EN50121-4
Immunity for Heavy Industrial Environment	EN61000-6-2
Emission for Heavy Industrial Environment	EN61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B
	EN61000-4-3 (RS) Level 3, Criteria A
	EN61000-4-4 (Burst) Level 3, Criteria A
	EN61000-4-5 (Surge) Level 3, Criteria B
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-6 (CS) Level 3, Criteria A
	EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A
Safety	UL 61010-2-201, EN62368-1
Surge Protection	4KV for PoE, UTP and Fiber ports
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-31
Vibration	IEC 60068-2-6

*Future release

Software Specifications

Topology

VLAN	IEEE 802.1q VLAN, up to 4094 802.1Q VLAN ID IEEE 802.1q VLAN, up to 4094 Groups IEEE 802.1ad Q-in-Q MAC-based VLAN, up to 256 entries IP Subnet-based VLAN, up to 128 entries Protocol-based VLAN (Ethernt, SNAP, LLC), up to 128 entries VLAN Translation, up to 256 entries Private VLAN for port isolation GVRP (GARP VLAN Registration Protocol) MVR (Multicast VLAN Registration) Voice VLAN
Link Aggregation (Port Trunk)	Static (Hash with SA, DA, IP, TCP/UDP port), up to 6 trunk group Dynamic (IEEE 802.3ad LACP), up to 6 trunk group
Spanning Tree	IEEE 802.1D STP, IEEE 802.1W RSTP, IEEE 802.1S MSTP
MRP (IEC62439-2)	Supported
Multiple μ-Ring	Up to 5 instances that each supports μ -Ring, μ -Chain or Sub-Ring type for flexible uses, and maximum up to 5 Rings Recovery time <20ms The maximum number of device is allowed 250 nodes in a Ring.
Loop Protection	Supported
ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection)	Recovery time <50ms Single Ring, Sub-Ring, Multiple ring topology network
ITU-T G.8031 / Y.1342 EPS (Ethernet Protection Switching)	Supported

QoS Features

Class of Service	IEEE 802.1p 8 active priorities queues for per port
Traffic Classification QoS	IEEE 802.1p based CoS, IP Precedence based CoS, IP DSCP based CoS QCL (QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI, Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number

Industrial Managed 10G PoE Switch

Bandwidth Control for Ingress	100~1,000,000 when the "Unit" is "kbps", and 1~1,000 when the "Unit" is "Mbps"
Bandwidth Control for Egress	100~1,000,000 when the "Unit" is "kbps", and 1~1,000 when the "Unit" is "Mbps" Per queue / Port shaper
DiffServ (RF 2474) Remarking	
Storm Control	For Unicast, Broadcast and Multicast
IP Multicasting Features	
IGMP / MLD Snooping	IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2 Port Filtering Profile Throttling Fast Leave Maximum Multicast Group : up to 1022 entries Query / Static Router Port
Security Features	
IEEE 802.1X	Port-Based MAC-Based
ACL	Number of rules : up to 256 entries for L2 / L3 / L4 L2 : Mac address SA/DA/VLAN L3: IP address SA/DA, Subnet L4: TCP/UDP
RADIUS	Authentication & Accounting
TACACS+	Authentication, Authorization and Accounting
HTTPS, HTTP	Supported
SSL / SSH v2	Supported
User Name Password Authentication	Local Authentication Remote Authentication (via RADIUS / TACACS+)
Management Interface Access Filtering	Web, Telnet / SSH, CLI USB console
Management Features	
CLI	Cisco® like CLI
Web UI	Supported
Telnet	Server
SNMP	V1, V2c, V3
sFlow	Supported
Modbus/TCP	Supports for management and monitoring
SW & Configuration Upgrade	SFTP, TFTP, HTTPS, HTTP, FTP Redundant firmware in case of upgrade failure
FTP Client	Supports for upload/download configuration
RMON	RMON I (1, 2, 3, 9 group), RMON II
MIB	RFC1213 MIB II, Private MIB
UPnP	Supported
DHCP v4	Server, Client, Relay, Relay option 82, Snooping
ARP Inspection	Supported
IP Source Guard	Supported
Port Mirroring	Supported
Event Syslog	Syslog server (RFC3164) (Support 4 server)
Warning Message	System syslog, e-mail, alarm relay
DNS	Client, Proxy
IEEE1588 PTP V2	Supports 5 operating mode in each port: Ordinary-boundary, peer to peer transparent clock, end to end transparent clock, master and slave
NTP V4.0, SNTP	Client
LLDP (IEEE 802.1ab)	Link Layer Discovery Protocol LLDP-MED



IPv6 Features

IPv6 Management	Telnet Server/ICMP v6
SNMP over IPv6	Supported
HTTP over IPv6	Supported
SSH over IPv6	Supported
IPv6 Telnet	Supported
IPv6 NTP, SNTP	Client
IPv6 TFTP	Supported
IPv6 QoS	Supported
IPv6 ACL	Number of rules: up to 256 entries for L2 / L3 / L4 L2 : Mac address SA/DA/VLAN L3: IP address SIP, Subnet (32bit) L4: TCP/UDP
IPv6 Source Guard	Supported
DHCP v6	Relay, Snooping


Others Features

Green Ethernet	Determine the cable length and lowering the power for ports with short cables Lower the power for a port when there is no link
-----------------------	---

Advanced PoE

Management	PoE PD failure auto checking, and auto reset when PD fail PoE port on/off weekly scheduling PoE Configuration PoE Enable/Disable Power limit by classification Power feeding priority Total PoE power budget limitation: maximum 240W
-------------------	---

Dimensions



Ordering Information

Model Name	Total Port	RJ45	SFP	PoE		Power Input	Certification			Operating Temperature
		10/100/1000 Base-T(X)	100M/1G/2.5G/10G	IEEE802.3 at/af	Power Budget	Redundant	EN50121-4	EN61000-6-2 EN61000-6-4	CE FCC	
IGS-A804XSM-8PH	12	8	4	8	240W	48VDC	V	V	V	-10~60°C

9

Optional Accessories

■ Auto Backup Kit

BUK1-USB	Backup kit for USB Type-C Console Managed Switch
----------	--

■ Wall Mount Kit

IND-WMK02	Wall Mount kit for Industrial product (Wide) (184 x 50mm)
-----------	---

■ Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with all CTC Union industrial grade Ethernet switches for guaranteed compatibility and performance. Best performance can be guaranteed, even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheets for more items and detailed information.)

ISFP-M7000-85-D(E)	Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-S7020-31-D(E)	Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-T7T00-00-(E)	Industrial SFP 10/100/1000Base-T UTP 100meter, -10~70°C (-40~85°C)
ISFP-M5002-31-D(E)	Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDMI, -10~70°C (-40~85°C)
ISFP-S5030-31-D(E)	Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDMI, -10~70°C (-40~85°C)

■ Industrial Power Supply

NDR-480-48	Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 480W, -20 ~ 70°C
XDR-240E-48	Industrial Power, Input 85 ~ 264VAC/120 ~ 370VDC, Output 48VDC, 240W, -40 ~ 70°C
XDR-480E-48	Industrial Power, Input 85 ~ 264VAC/120 ~ 370VDC, Output 48VDC, 480W, -40 ~ 70°C