

ITR-AG804TM-8PHE24i & ITR-AG804TM-8PHE-WWi

- ◀ 12x GbE M12 with 8x PoE 60W, 24/48VDC
- ▶ 12x GbE M12 with 8x PoE 60W, 24/48/72/96/110VDC

- ◆ L3 IPV4/IPV6 Static Routing, RIP v1/v2 Dynamic Routing, OSPF v2/v3 Dynamic Routing
- ◆ Compliant with the IEC 62443-4-2* Industrial Cybersecurity Standards
- ◆ EN50155, EN50121-4, EN45545-2, EN61000-6-2, EN61000-6-4, CE and FCC Certified
- ◆ 24/48/72/96/110VDC Redundant Dual Power Input
- ◆ Supports Power Isolation
- ◆ Regulated PoE Output Voltage
- ◆ Auto Checking and Auto Reset when PoE PD Fail
- ◆ Build-in 2 Bypass GbE UTP Port

Preliminary



The EN50155 certified and cyber-hardened managed PoE switches, ITR-AG804TM-8PHE24i and ITR-AG804TM-8PHE-WWi, deliver reliable, high-speed connectivity for rolling stock environments. They feature 12 Gigabit M12 X-code Ethernet ports that ensure secure and stable connections even under vibration and shock conditions. With Layer 3 routing capabilities, including IPv4/IPv6 static routing, RIP v1/v2, and OSPF v2/v3 dynamic routing, the switches enable flexible network segmentation and optimized data traffic management.

Compliant with the IEC 62443-4-2 cybersecurity standard, the ITR-AG804TM series ensures the security and stability of onboard and train-to-ground communications. This compliance strengthens protection against cyber threats and enhances the overall resilience of intelligent railway systems. In addition, the switches support ring redundancy to ensure reliable network failover and prevent system downtime caused by single-point failures.

The series also supports advanced PoE management functions, including auto power detection, intelligent power reset, and scheduling, improving energy efficiency and device uptime. With isolated 24/48 VDC or 24/48/72/96/110 VDC power inputs, the design supports voltage boosting to ensure stable PoE operation across diverse vehicle power systems. Certified to EN 50155 standards for temperature, voltage fluctuation, surge, ESD, vibration, and shock, the ITR-AG804TM series delivers long-term reliability in mission-critical rail and vehicle applications.

Features

- M12 connector against vibration and shock
- 24/48/72/96/110VDC redundant dual input power, and built-in power booster design up to 50VDC for PoE output
- Regulated PoE output voltage (50VDC) to stabilize PoE device, and guarantee delivery PoE power distance to 100meters
- Cable diagnostics, identifies opens/shorts distance
- Provides up to 5 instances that each supports μ-Ring, μ-Chain or Sub-Ring type for flexible uses.
(Please see CTC Union's μ-Ring white paper for more details)
- Supports TTDP for train application
- Supports EMS Management

Specifications

| Standard | IEEE 802.3 | 10Base-T 10Mbit/s Ethernet |
|----------|-----------------------|--|
| | IEEE 802.3u | 100Base-TX, 100Base-FX, Fast Ethernet |
| | IEEE 802.3ab | 1000Base-T Gbit/s Ethernet over twisted pair |
| | IEEE 802.3z | 1000Base-X Gbit/s Ethernet over Fiber-Optic |
| | IEEE 802.1D | STP (Spanning Tree Protocol) |
| | IEEE 802.1W | RSTP (Rapid Spanning Tree Protocol) |
| | IEEE 802.1S | MSTP (Multiple Spanning Tree Protocol) |
| | ITU-T G.8032 / Y.1344 | ERPS (Ethernet Ring Protection Switching) |

EN50155 Cyber-Hardened Managed PoE Switch



| | | | | | |
|------------------------------------|--|---|---------------------------------|-------------------|-------------------------|
| Standard | ITU-T G.8031 / Y.1342 | APS (Automatic Protection Switching) | | | |
| | IEEE 802.1Q | Virtual LANs (VLAN) | | | |
| | IEEE 802.1X | Port based and MAC based Network Access Control, Authentication | | | |
| | IEEE 802.3ac | Max frame size extended to 1522Bytes | | | |
| | IEEE 802.3ad | Link aggregation for parallel links with LACP (Link Aggregation Control Protocol) | | | |
| | IEEE 802.3x | Flow control for Full Duplex | | | |
| | IEEE 802.3af | PoE (Power over Ethernet) | | | |
| | IEEE 802.3at | PoE+ (Power over Ethernet enhancements) | | | |
| | IEEE 802.1ad | Stacked VLANs, Q-in-Q | | | |
| | IEEE 802.1p | LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization | | | |
| | IEEE 802.1ab | Link Layer Discovery Protocol (LLDP) | | | |
| | VLAN ID | 4094 IEEE802.1Q VLAN ID | | | |
| Switch Architecture | Back-plane (Switching Fabric): 24Gbps (Full wire-speed) | | | | |
| Data Processing | Store and Forward | | | | |
| Flow Control | IEEE 802.3x for full duplex mode Back pressure for half duplex mode | | | | |
| PoE RJ-45 Pin Assignment | 8x M12 (8-Pin X-code Female) ports support IEEE 802.3af / IEEE 802.3at End-Span, Alternative A mode. | | | | |
| Network Connector | 12x M12 (8-Pin, Female, X-Code) 10/100/1000Base-T UTP | | | | |
| | UTP port provides Auto negotiation speed, Auto MDI/MDI-X, Full/Half duplex function | | | | |
| | Build-in 2x bypass GbE UTP ports | | | | |
| Console | RS-232 (5-pin A-Code M12 male) | | | | |
| USB | 5-Pin M12 male | | | | |
| Network Cable | UTP/STP Cat. 5e cable or above | | | | |
| | EIA/TIA-568 100-ohm (100meter) | | | | |
| Protocols | CSMA/CD | | | | |
| Reverse Polarity Protection | Supported | | | | |
| Overload Current Protection | Supported | | | | |
| CPU Watch Dog | Supported | | | | |
| LED | System: Power 1 (Green), Power 2 (Green) | | | | |
| | UTP: 10/100 Link/Active (Green), 1000 Link/Active (Amber) | | | | |
| | PoE: ON (Green) | | | | |
| Jumbo Frame | 10KB | | | | |
| MAC Address Table | 16K | | | | |
| Memory Buffer | 12Mb for packet buffer | | | | |
| Device Memory | 4G Bytes eMMC, 2G Bytes RAM | | | | |
| PoE Standard | IEEE802.3af, IEEE802.3at | | | | |
| PoE Power Output | Maximum PoE output power budget 96W at 70°C, 60W at 75°C (Max 30W/port) Regulated PoE output voltage at 50VDC | | | | |
| Power Supply | Provides 1x M12 (5-Pin, male) for redundant dual DC 24/48V (20~57VDC) or DC 24/48/72/96/110V (16~130VDC) input power | | | | |
| | Built-in very high efficiency booster(94~97%) to rise up 50VDC for PoE output | | | | |
| | Regulated PoE output voltage (50VDC) to stabilize PoE device, and guarantee delivery PoE power distance to 100 meter | | | | |
| Power Consumption | Input Voltage | Total Power Consumption | Device Power Consumption | PoE Budget | Boost Efficiency |
| | 24 VDC | 80W | 13W | 60W | 95.6% |
| | 48 VDC | 81W | 14W | 60W | 95.9% |
| | 110VDC | 82W | 15W | 60W | N/A |
| Warning Message | System Syslog, SMTP/ e-mail event message | | | | |
| Operating Temperature | -40 ~ 75°C | | | | |
| Operating Humidity | 5% to 95% (Non-condensing) | | | | |
| Storage Temperature | -40 ~ 85°C | | | | |
| Housing | Rugged Metal, Fanless, IP40 grade housing for against water, dust, and oil | | | | |
| Dimensions | 116.5 x 184.6 x 118mm (D x W x H) | | | | |
| Weight | TBD | | | | |
| Installation Mounting | Wall mounting or DIN Rail mounting (Optional) | | | | |
| MTBF | TBD (MIL-HDBK-217) | | | | |
| Warranty | 5 years | | | | |

Certification

| | |
|--|---|
| Industrial Cybersecurity | IEC 62443-4-1, IEC 62443-4-2* |
| EMC | CE |
| EMI (Electromagnetic Interference) | FCC Part 15 Subpart B Class A, CE |
| Railway Traffic | EN50155, EN50121-4 |
| Fire protection of railway vehicles | EN45545-2 |
| Immunity for Heavy Industrial Environment | EN61000-6-2 |
| Emission for Heavy Industrial Environment | EN61000-6-4 |
| EMS (Electromagnetic Susceptibility) Protection Level | EN61000-4-2 (ESD) Level 3, Criteria B |
| | EN61000-4-3 (RS) Level 3, Criteria A |
| | EN61000-4-4 (Burst) Level 3, Criteria A |
| | EN61000-4-5 (Surge) Level 3, Criteria B |
| | EN61000-4-6 (CS) Level 3, Criteria A |
| | EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A |
| Shock | IEC-61373 |
| Freefall | IEC 60068-2-32 |
| Vibration | IEC-61373 |

*Future release

Software Specifications

Topology

| | |
|--|---|
| VLAN | IEEE 802.1q VLAN, up to 4094 802.1Q VLAN ID |
| | IEEE 802.1q VLAN, up to 4094 Groups |
| | IEEE 802.1ad Q-in-Q |
| | MAC-based VLAN, up to 256 entries |
| | IP Subnet-based VLAN, up to 128 entries |
| | Protocol-based VLAN (Ethernet, SNAP, LLC), up to 128 entries |
| | VLAN Translation, up to 256 entries |
| | Private VLAN for port isolation |
| | GVRP (GARP VLAN Registration Protocol) |
| | MVR (Multicast VLAN Registration) |
| | Voice VLAN |
| Link Aggregation (Port Trunk) | Static (Hash with SA, DA, IP, TCP/UDP port), up to 6 trunk group |
| | Dynamic (IEEE 802.3ad LACP), up to 6 trunk group |
| Spanning Tree | IEEE802.1D STP, IEEE802.1W RSTP, IEEE802.1S MSTP |
| MRP (IEC 62439-2) | Supported |
| Multiple μ-Ring | Up to 5 instances that each supports u-Ring, u-Chain or Sub-Ring type for flexible uses, and maximum up to 5 Rings. |
| | Recovery time <20ms |
| | The maximum number of device is allowed 250 nodes in a Ring. |
| Loop Protection | Supported |
| ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection) | Recovery time <50ms |
| | Single Ring, Sub-Ring, Multiple ring topology network |
| ITU-T G.8031 / Y.1342 EPS (Ethernet Protection Switching) | Supported |

QoS Features

| | |
|-----------------------------------|--|
| Class of Service | IEEE802.1p 8 active priorities queues per port |
| Traffic Classification QoS | IEEE802.1p based CoS |
| | IP Precedence based CoS |
| | IP DSCP based CoS |
| | QCL (QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI, Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number |

EN50155 Cyber-Hardened Managed PoE Switch

| | |
|--|--|
| Bandwidth Control for Ingress | 100~1,000,000 when the "Unit" is "kpbs" and 1~1,000 when the "Unit" is "Mbps" |
| Bandwidth Control for Egress | 100~1,000,000 when the "Unit" is "kpbs" and 1~1,000 when the "Unit" is "Mbps" Per queue / Port shaper |
| DiffServ (RF 2474) Remarking | |
| Storm Control | For Unicast, Broadcast and Multicast |
| IP Multicasting Features | |
| IGMP / MLD Snooping | IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2 Port Filtering Profile, Throttling Fast Leave Maximum Multicast Group : up to 1022 entries Query / Static Router Port |
| Security Features | |
| IEEE 802.1X | Port-Based, MAC-Based |
| ACL | Number of rules : up to 256 entries for L2 / L3 / L4 L2: Mac address SA/DA/VLAN L3: IP address SA/DA, Subnet L4: TCP/UDP |
| RADIUS | Authentication & Accounting |
| TACACS+ | Authentication, Authorization, Accounting |
| HTTPS, HTTP | Supported |
| SSL / SSH v2 | Supported |
| User Name Password Authentication | Local Authentication Remote Authentication (via RADIUS / TACACS+) |
| Management Interface Access Filtering | Web, Telnet / SSH, CLI RS-232 console |
| Management Features | |
| CLI | Cisco® like CLI |
| Web UI | Supported |
| Telnet | Server |
| SNMP | V1, V2c, V3 |
| sFlow | Supported |
| Modbus/TCP | Supports for management and monitoring |
| SW & Configuration Upgrade | SFTP, TFTP, FTP, HTTPS, HTTP Redundant firmware in case of upgrade failure |
| FTP client | Supports for upload/download configuration |
| RMON | RMON I (1, 2, 3, 9 group), RMON II |
| MIB II | RFC 1213 MIB II, Private MIB |
| UPnP | Supported |
| DHCP | Server, Client, Relay, Relay option 82, Snooping |
| RARP | Supported |
| TTDP | Supported (Train Topology Discovery Protocol) |
| IP Source Guard | Supported |
| Port Mirroring | Supported Syslog server (RFC3164) (Supports 4 Server) |
| Warning Message | System syslog, e-mail |
| DNS | Client, Proxy |
| NTP, SNTP | Client |
| LLDP (IEEE 802.1ab) | Link Layer Discovery Protocol LLDP-MED |
| IPv6 Features | |
| IPv6 Management | Telnet Server/ICMP v6 |
| SNMP over IPv6 | Supported |
| HTTPS, HTTP over IPv6 | Supported |



5

| | |
|--------------------------------|---|
| SSH over IPv6 | Supported |
| IPv6 Telnet | Supported |
| IPv6 NTP, SNTP | Client |
| IPv6 TFTP | Supported |
| IPv6 QoS | Supported |
| IPv6 ACL | Number of rules: up to 256 entries for L2 / L3 / L4 L2: Mac address SA/DA/VLAN L3: IP address SIP, Subnet (32bit) L4: TCP/UDP |
| Others Features | |
| Green Ethernet | Determine the cable length and lowering the power for ports with short cables Lower the power for a port when there is no link |
| Cable Diagnostic | Measuring UTP cable OK or broken point distance |
| Advanced PoE Management | PoE PD Failure Auto Checking, and Auto reset when PD fail PoE Scheduling (On/Off schedule weekly) PoE Configuration PoE Enable/Disable Power limit by classification Power limit by management Total PoE Power budge (maximum 96W at 70°C, 60W at 75°C) limitation |

Ordering Information

| Model Name | Managed | Total Port | UTP M12 | | PoE | PoE Total Power Budget | Power Input | | Certification | | | | Operating Temperature |
|----------------------|---------|------------|--------------------|--------------|-----|------------------------|-------------|-------------------|---------------|-------------------------|--------|----------|-----------------------|
| | | | 10/100/1000 Base-T | IEEE 802.3at | | | Redundant | EN50155 EN50121-4 | EN45545-2 | EN61000-6-2 EN61000-6-4 | CE FCC | | |
| ITR-AG804TM-8PHE24i | V | 12 | 12 (X-Code) | 8 | 60W | 24/48VDC | V | V | V | V | V | -40~75°C | |
| ITR-AG804TM-8PHE-WVi | V | 12 | 12 (X-Code) | 8 | 60W | 24~110VDC | V | V | V | V | V | -40~75°C | |

Optional Accessories

Optional Cable/Connector & Din-Rail Kit

P/N: CAB-M12XM8-RJ45

M12 X-code Male (8-Pin) to RJ-45, AWG 24 ,IP67, 1 meter



For GbE UTP (X-code model)

P/N: CAB-M12KF5-OPEN

M12 K-code Female (5-Pin) to open wire , AWG 16 , IP67, 1 meter



For Power

P/N: M12X-M8

M12 X-code Male (8-Pin) connector, IP67



For GbE UTP (X-code model)